MAGNETIC OIL DRAIN PLIER



1. FEATURES

2. SPECIFICATION

3. INSTRUCTION

4. RELATED ITEMS

1. FEATURES

- ▶ Drain old and hot engine oil, transmission fluid, gear oil without danger.
- ► High power magnet grips oil plug well.
- ▶ Pleasant oil changing works.
- ▶ Patented handle provide comfortable gripping.
- ► Universal application.
 - Always read complete the instruction manual before working.
 - $igodoldsymbol{$ This tool is ONLY available to drain oil from automobile.
 - \blacklozenge Always wear eye protection that meets OSHA and ANSI Z87.1 standards.
 - \blacklozenge Always wear gloves when work with the tool.
 - \blacklozenge Ensure the work area has adequate lighting.
 - $igodoldsymbol{\in}$ Keep children and unauthorised people away from the work area.
 - \blacklozenge Keep work area clean and tidy, dry and free from unrelated materials.
 - DO NOT allow untrained people to use the kit.

2. SPECIFICATION



A - HIGH POWER MAGNET				
Size	17.9mm			
Thickness	3mm			
Max. Working Temperature	120 degrees			
B- MAGNET HOLDER				
Angle	90 degrees			
Material	Steel			
Surface finish	Chrome			
Width	22 mm			
Height	13.5 mm			
C- WIRE				
Material	Steel wire			
Size	1/8"			
Length	185 mm			
D- PATENTED HANDLE				
Material	Plastic			
Color	Black			



3. INSTRUCTION



STEP 2) Install high power magnetic drain plier onto drain plug. (Fig.2 Fig.3)







(Fig.3)

(Fig.1)



Release oil drain plug continually until removal. (Fig.4 Fig.5)





COMPARISON

(Fig.4)

(Fig.5)









 SAFE DISTANCE
 Second Secon



4. RELATED ITEMS



OIL DRA	IN PLUG	REPAIR	KIT	SERIES
---------	---------	--------	-----	--------

This series is designed for replacing the damaged oil drain nuts by using a tap to enlarge / rethreading the stripped drain plug hole for fitting new nuts with bigger sizes.

M13 x 1.5P
M13 x 1.25P
M14 x 1.25P
M15 x 1.5P
M17 x 1.5P
M18 x 1.5P
M20 x 1.5P
M22 x 1.5P



3/8" DRAIN NUT SET

Set includes 14 sockets with different sizes for transmission, differential and gear oil drain plugs. Set also includes a sliding T-bar.

SPECIFICATIONS:

 8mm HEX- 9mm HEX- 9.5mm (3/8")- 10mm HEX- 12mm HEX- 14mm HEX- 17mm HEX- 	BMW (BA), FORD (GB), GM (BA, GB) GENERAL MOTORS (BA) BLMC (MORRIS) (BA), LANCIA BETA (DIFF) FORD (GB),TOYOTA FIAT, LANCIA (GB, SU), PEUGEOT TALBOT (GB, SU) LANCIA (GB, SU), MERCEDES-Benz (BA, GB) LANCIA, AUDI (GB), AUSTIN (GB), BMW (GB), VW(GB)
8 mm (5/16")-	CITROËN (GB, SU), PEUGEOT (BA, GB, SU), RENAULT (SU), TALBOT (GB, SU), VOLVO (SU)
9.5mm(3/8")-	HONDA (GB, SU), MAZDA (BA, GB), PEUGEOT (GB, SU), SAAB (GB), VOLVO (BA, SU)
🗖 11mm-	FORD (BA, GB)
12mm-	ΤΟΥΟΤΑ
13mm-	NISSAN (BA, GB), SUBARU (BA)
🗂 10mm-	BMW, FORD, RENAULT, TOYOTA
▲ 3/8″-	RENAULT



TOYOTA DIFFERENTIAL DRAIN SOCKET SET (2 pcs)

3/8"DR - 24mm hex	3/8″DR - 10mm hex
Toyota 4WD vehicles	Toyota 4WD vehicles
(models before 2007)	(models after 2007)

The 24mm socket is 22mm in height, which makes differential services in limited space much easier.



