

1/4" screwdriver bit sets

Intended for tightening and loosening screw in places that are difficult to access. They include the most popular bits made of strong chromium-vanadium steel and a 60 mm adapter (sets 66301 and 66302). Packed into handy cassettes with legible bit type markings.

56
PCS

66310

- ▯ 1/4" (6.3 mm): 3, 4, 5, 5.5, 6, 7 mm (L=25 mm); 4, 6 mm (L=50 mm); CrV;
- ⊕ PH0, 2 x PH1, 5 x PH2, PH3 (L=25 mm); PH1, PH2, PH3 (L=50 mm); CrV;
- ⊖ PZ0, 2 x PZ1, 5 x PZ2, PZ3 (L=25 mm); PZ1, PZ2, PZ3 (L=50 mm); CrV;
- ⊗ T10, T15, T20, T25, T27, T30, T40 (L=25 mm); T15, T20, T25 (L=50 mm); CrV;
- 1/4" (6.3 mm): 2, 2.5, 3, 4, 5, 5.5, 6 mm (L=25 mm); 4, 5, 6 mm (L=50 mm); CrV;
- 1/4" (6.3 mm): S0, S1, S2, S3 (L=25 mm); CrV



41
PCS

66301

- ▯ 1/4" (6.3 mm): 3, 4, 5, 5.5, 6, 7 mm (L=25 mm); CrV;
- ⊕ 1/4" (6.3 mm): PH0, 2 x PH1, 4 x PH2, PH3 (L=25 mm); CrV;
- ⊖ 1/4" (6.3 mm): PZ0, 2 x PZ1, 4 x PZ2, PZ3 (L=25 mm); CrV;
- ⊗ 1/4" (6.3 mm): T10, T15, T20, T25, T27, T30, T40 (L=25 mm); CrV;
- 1/4" (6.3 mm): 2, 2.5, 3, 4, 5, 5.5, 6 mm (L=25 mm); CrV;
- 1/4" (6.3 mm): S0, S1, S2, S3 (L=25 mm); CrV;
- ▯ 1/4" (6.3 mm), (L=60 mm)

31
PCS

66302

- ▯ 1/4" (6.3 mm): 3, 4, 5, 5.5, 6, 7 mm (L=25 mm); CrV;
- ⊕ 1/4" (6.3 mm): PH0, 2 x PH1, 2 x PH2, PH3 (L=25 mm); CrV;
- ⊖ 1/4" (6.3 mm): PZ0, 2 x PZ1, 2 x PZ2, PZ3 (L=25 mm); CrV;
- ⊗ 1/4" (6.3 mm): T10, T15, T20, T25, T27, T30 (L=25 mm); CrV;
- 1/4" (6.3 mm): 2, 3, 4, 5, 5.5, 6 mm (L=25 mm); CrV;
- ▯ 1/4" (6.3 mm), (L=60 mm)

