

Service cabinet with 302 tools

58550

302 PCS
12 TRAYS

975x765
x465 mm

6x

BALL
BEARING

25kg
35kg

NON
SLIP
POLYPROPYLENE
WORKTOP

125
mm
WHEELS

2x
BRAKE

2x
BRAKE

DRAWERS
LOCKING

DOUBLE
WALLS


DOUBLE
WALLS

UNIVERSAL
PERFORATION

UNIVERSAL
PERFORATION



CORNER BUMPERS



12 exchangeable inserts with Sthor tools:



1/2" (12.7 mm): 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 27, 30, 32 mm; CrV;

1/2" (12.7 mm); 45T; CrV;

1/2" (12.7 mm); CrV;

1/2" (12.7 mm): 16, 21 mm; CrV;

1/2" (12.7 mm); CrV



3/8" (9.5 mm): 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22 mm; CrV;

3/8" (9.5 mm) x2; CrV;

3/8" (9.5 mm); CrV;

3/8" (9.5 mm); 45T; CrV;

3/8" (9.5 mm); CrV



1/4" (6.3 mm): 3.5, 4.0, 4.5, 5.0, 5.5, 6.0, 7.0, 8.0, 9.0, 10.0, 11.0, 12.0, 13.0, 14.0; CrV;

1/4" (6.3 mm): E4, E5, E6, E7, E8; CrV;

1/4" (6.3 mm); CrV;

1/4" (6.3 mm) x2; CrV;

1/4" (6.3 mm); CrV;

1/4" (6.3 mm); CrV;

1/4" (6.3 mm); 45T; CrV;

1/4" (6.3 mm) x 1/4" (6.3 mm); CrV 50BV30;

1/4" (6.3 mm): 3, 4, 5.5, 6.5, 7, 8, 9;

1/4" (6.3 mm): PH0, PH1, PH2, PH3;

1/4" (6.3 mm): PZ0, PZ1, PZ2, PZ3;

1/4" (6.3 mm): T8, T9, T10, T15, T20, T25, T27, T30;

1/4" (6.3 mm): T8, T9, T10, T15, T20, T25, T27, T30;

1/4" (6.3 mm): 3, 4, 5, 6, 7, 8 mm;

1/4" (6.3 mm): S0, S1, S2;

1/4" (6.3 mm): 4, 5.5, 6.5 mm; CrV;

1/4" (6.3 mm): PH1, PH2; CrV;

1/4" (6.3 mm): PZ1, PZ2; CrV;

1/4" (6.3 mm): T8, T10, T15, T20, T25; CrV;

1/4" (6.3 mm): T10, T15, T25, T40; CrV;

1/4" (6.3 mm): 3, 4, 5, 6 mm; CrV



3/8" (9.5 mm): 4, 5, 6, 7, 8, 10, 12 mm (L=30 mm); 4, 5, 6, 7, 8, 10, 12 mm (L=75 mm); AISI S2;

3/8" (9.5 mm): M5, M6, M8, M10, M12 (L=30 mm); M5, M6, M8, M10, M12 (L=75 mm); AISI S2;

1/2" (12.7 mm) x 3/8" (9.5 mm), 3/8" (9.5 mm) x 3/8" (9.5 mm); CrV 6150

3/8" (9.5 mm): T20, T25, T30, T40, T45, T50, T55 (L=30 mm); T20, T25, T30, T40, T45, T50, T55 (L=75 mm); AISI S2;



1/2" (12.7 mm): 14, 15, 17, 19, 22 mm; CrV;

1/2" (12.7 mm): E18, E20, E24; CrV;

3/8" (9.5 mm): E10, E11, E12, E14, E16; CrV;

1/2" (12.7 mm); CrV;

1/2" (12.7 mm); CrV



6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21 mm



5/32" (4 mm); CrV 6150;

5/32" (4 mm); CrV 6150;

5/32" (4 mm): 1.0, 1.5, 2.0, 2.5, 3.0, 3.5 mm; CrV 6150;

5/32" (4 mm): PH000, PH00, PH01, PH1; CrV 6150;

5/32" (4 mm): PZ0, PZ1; CrV 6150;

5/32" (4 mm): T4, T5, T6, T7, T8, T9, T10, T15, T20; CrV 6150;

5/32" (4 mm): 0.7, 0.9, 1.3, 2.0, 2.5, 3.0, 4.0 mm; CrV 6150;

5/32" (4 mm): 2.5, 3.0, 3.5, 4.0, 4.5, 5.0, 5.5 mm;

CrV;

2.0, 2.5, 3.0, 4.0, 5.0, 5.5, 6.0, 8.0, 10.0 mm; CrV;

T10, T15, T20, T25, T27, T30, T40, T45, T50; CrV



EXTERNAL STRAIGHT

INTERNAL STRAIGHT

EXTERNAL BENT

INTERNAL BENT



LONG NOSE;



LONG NOSE;



300 g;



Ø 28 mm;



12x150, 16x170 mm;




6x100, 2x140 mm;



1.5x150, 3x150, 5x150, 8x150 mm



3x75, 5x100, 6x100, 8x150 mm; CrV;



PH0x75, PH1x100, PH2x100, PH3x150 mm; CrV



300 mm;



300 mm;



300 mm;



300 mm;



300 mm