

Measuring rulers

Flexible measures with millimeter scale and conversion table. Suitable for fast and precise measurements and determination of straight lines in marking, locksmithing, carpentry and decoration work.

- made of stainless steel
- durable, double-sided millimetre graduation
- conversion tables for easy conversion of mm/inch values on the reverse side
- width of the ruler: 19 mm

	CONVERSION TABLE		
in	mm		
2 = 3 = 4 = 1 5 = 1	25.400 50.800 76.200 01.600 27.000 52.400		
1/4 =	2.70000 6.35000 9.05000		
	9.00000		

ΥΑΤΟ Ъ	L (mm)
YT-70720	150
YT-70721	300
YT-70722	500
YT-70723	600
YT-70724	1000



YATO		720	
AIO		1-70	
×	2	7	
=	-	=	
=	4	=	
=	-		
	~	_	
_			
_	0126 9 × 10 11 12 13 14 15		
	12		
_			
	-	=	
	-	=	
	0		
_	-	=	
_	3		
	6	=	
	1126		
_ ∞		∞ <u> </u>	
_	M19	=	
=~		_	
	Y	=	
	~	=	
=	0 -	=	
		=	
=	1 5		
	Ξ		
=	4 -		
=		_	
	m -	=	
		=	
		=	
	2-12	=	
	E	=	
	.15m 1cm		
	.15m		
_	0	=	



CONVERSION TABLE
in mm
1 = 25.400 2 = 50.800 3 = 76.200 4 = 101.600 5 = 127.000 6 = 152.400 1/2 = 12.7000 1/4 = 6.35000 3/4 = 19.05000 1/6 = 3.3500 1/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.3500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/6 = 3.5500 3/7 = 3.5500 3/7 = 3.5500 3/7 = 3.5500 3/7 = 3.5500 3/7 = 3.5500 3/7 = 3.5500 3/7 = 3.5500 3/7 = 3.5500 3/7 = 3.5500 3/7 = 3.5500 3/7 = 3.5500 3/7 = 3.5500 3/7 = 3.5500 3/7 = 3.5500 3/7 = 3.5500 3/7 = 3.5500 3/7 = 3.5500 3/7 = 3.5500 3/7 = 3.5500 3/7 = 3.5500 3/7 = 3.5500 3/7 = 3.5500 3/7 = 3.5500 3/7 = 3.5500 3/7 = 3.5500 3/7 = 3.5500 3/7 = 3.5500 3/7 = 3.5500 3/7 = 3.55000 3/7 = 3.5500 3/7 = 3.55000 3/7 = 3.55000 3/7 = 3.55000 3/7 =
1/2 = 12.70000 1/4 = 6.35000
1/4 = 6.35000 3/4 = 19.05000
1/8 = 3.17500 3/8 = 9.52500 5/8 =15.87500 7/8 =22.22500
1/16= 1.58750 3/16= 4.76250 5/16= 7.93750 7/18= 11.11250 9/16= 11.426750 11/16= 17.46250 13/16= 20.63750 15/16= 23.81250
1/12 = 0.79375 3/22 = 2.38125 5/22 = 3.98875 7/12 = 5.55625 9/12 = 7.14375 1/22 = 10.31815 1/522 = 11.90625
17/2 = 13.49375 19/2 = 15.08125 21/2 = 16.68875 23/2 = 18.25625 23/2 = 19.84375 27/2 = 21.43125 24/2 = 23.01875 31/3 = 24.60625
TAP DRILL
(11,11) (11,11) M 1 0.75 M 3 50
H 12 0.05 H 7 6.0 M 14 1.10 M 8 6.8 M 17 1.35 M 9 7.8 M 2 160 M 10 85 M 2 160 M 10 85 M 2 160 M 10 85 M 2 160 M 12 102 M 2 4.15 M 4 120 M 32.44 M 3 2.40 M 16 140 M 35.240 M 4 3.25 M 20 115 M 4 3.25 M 20 115 M 4 3.26 M 20 115 M 5 3.11 M 24.21.0 M 55.45 M 55.45 M 27 24.0
W.W UNF
(Min) (Min) W 1/4 5.1 U 1/4 5.2
W 14 51 U 1/4 52 W 516 66 U 5/16 66 W 5/6 60 U 5/16 66 W 7/6 6 U 4/7 16 93 W 1/2 107 U 1/2 108 W 9/6 1/2 U 9/16 128 W 5/6 1/3 U 5/6 13.6 W 3/4 16 7/U 3/4 16 5 W 7/8 105 U 7/8 19.5 W 1 224 U 1 223

www.yato.com